



Airtop Superior

Super premium synthetic air compressor lubricant

Description

Airtop Superior represents Matrix continued leadership in producing exceptional performance compressor fluids. These are PAO based and ashless. The antiwear additives provide high performance and oxidation stability and good corrosion protection.

- Reduced maintenance cost
- Very long fluid life
- Energy savings
- Reduced downtime
- Long service life
- Excellent materials compatibility
- Excellent rust & corrosion control

Properties

- Superior oxidation stability
- Good demulsification
- Excellent filterability
- High load carrying capacity

Performance level

Meets and exceeds the performance requirements of:

- DIN 51506 (VBL, VCL, VDL)

Typical performance data

	46	68	100	150
Colour	Clear yellowish			
Viscosity Index	>140	>140	>140	>160
Viscosity @ 40 °C, cSt	42-50	62-74	90-110	135-165
Viscosity @ 100 °C, cSt	7-9	9-11	13-15	18-20
Flash point, °C	>220	>220	>230	>230
Pour point, °C	<-45	<-35	<-30	<-30
Foaming seq. I	0/0	0/0	0/0	0/0
Demulsibility 30 min.	40/38/2	40/38/2	40/38/2	40/38/2

All performance data on this Technical Data Sheet are indicative only and can vary during production

Matrix Specialty Lubricants BV - info@lubes-portal.com - www.lubes-portal.com